


## ■ Powerful and reliable 3D orbital motion

- Gentle 3D motion and sturdy construction for high capacity
- Continuous or timed operation
- Standard elastic ties for easy fitting of flasks and conical tubes
- Optional second platform available to double the working area, large upper platform for variety of flasks and tubes
- Non-slip mat as standard, optional dimpled pad prevents tubes from rolling around
- Rubber bellows for protecting the user's finger from inadvertent accident

- An examples to use
- Western blotting
  - Gel staining
  - Immunoprecipitation
  - Bacteria / Yest culture



3D motion 7° tilt angle



► TW3



### Specification

Model	TW3
Tilt Angle	±7°
Speed Range	8 ~ 70 rpm
Motor	DC Warm Gear Motor
Timer (Speed )	180min
Temp. Resist	Lower than 65°C(Dry air)
Loadable Weight	5Kg
Weight	9Kg
Dimensions (mm)	W330xD330xH178
Platform (mm)	W300xD300
Wattage	35W
Power	Free Voltage (AC 100-240V)
Frequency	50/60Hz

### Accessories

Model Number	Description
DP-300	Dimpled Pad (W300 X D300 mm)
TY300	Second platform, (with posts : 4ea)
UP400	Upper platform (W400 X D400 mm)

### ACCESSORIES



DP-300



TY300



UP400